

A custom-made sign that can be adapted to the most demanding designs thanks to the point-by-point installation of LEDs.



OUR COMMITMENTS



Signs with a high level of customization



21-days lead time from validation of technical drawings to delivery



IP68



Up to 5 year guarantee







CARACTERISTIQUES

PRODUCT SPECIFICATION

Material: PMMA (Acrylic)

Paint: RAL® or Pantone®

Vinyl: 3M® 3630 and Avery Dennison® 4500TF

Mounting: Threaded rods / Spacer / Snap System / Easy-fix

Voltage: 12 V

Production: CE-certified components

Protection rating: IP 68

Sign resistance: -10 to 50 degrees

Fire class certification: PMMA certificate (M4)

LED SPECIFICATION

Brightness: Up to 2100 cd/m²

LED source LUM flux: 50 Lumen

Efficiency of finished product: 80 Lumen/watt

Power consumption per LED (white): 0.07 Watt

Life span: 80% to 10,000 hours


LED color specified: Yes

Dimmable: Yes


Installation of replacement letters: Yes



DIFFERENT LIGHTING EFFECTS



TECHNICAL DRAWING



- 1 Block of embedded LEDs 3/4" to 1-1/2" thick
- 2 Illuminated face (acrylic) with vinyl or painted (RAL® or PANTONE®)
- 3 Illuminated return (acrylic) or painted (RAL® OR PANTONE®)
- 4 3/8" is the minimum necessary to embed an LED
- I. Acrylic is milled
 II. LEDs are embedded inside the acrylic
 III. LEDs are covered with a thin layer of resin to make the sign waterproof



THE KALISIGN SPIRIT

Tailor-made personalized solutions with a wide choice of:

- Brass and Stainless steel
- PT® and Respect® acrylics
- C RAL® and Pantone® paint
- Uinyls from the 3M[®] 3630 and Avery Dennison[®] 4500TF



Please note: vinyl only fits on the front and back of the sign.

Possibility of mounting on an acrylic backer with the cables hollowed out inside.

SPECIFIC REQUEST

Thanks to our excellent savoir-faire, we can offer you a wide range of customisation options. Contact our team to find out more!