

DATA SHEET

A custom-made sign that can be adapted to the most demanding designs thanks to the dot by dot installation of LEDs.



OUR COMMITMENTS



Signs with a high level of customization



21-days lead time from validation of technical drawings to delivery







SPECIFICATIONS

PRODUCT SPECIFICATION
Material: PMMA (Acrylic)
Paint: RAL® or Pantone®
Vinyl: 3M [®] 3630 and Avery Dennison [®] 4500TF
Mounting: Threaded rods / Spacer / Snap System / Easy-fix
Voltage: 12 V
Production: CE-certified components
Protection rating: IP 68
Sign resistance: -10 to 50 degrees
Fire class certification: PMMA certificate (M4)

LED SPECIFICATION

Brightness: Up to 2100 cd/m² LED source LUM flux: 50 Lumen Efficiency of finished product: 80 Lumen/watt Power consumption per LED (white): 0.07 Watt Life span: 80% to 10,000 hours LED color specified: Yes Dimmable: Yes Installation of replacement letters: Yes







THE KALISIGN SPIRIT

Tailor-made personalized solutions with a wide choice of:

- Brass and Stainless steel
- PT[®] and Respect[®] acrylics
- RAL[®] and Pantone[®] paint
- Uinyls from the 3M[®] 3630 and Avery Dennison[®] 4500TF

Please note: vinyl only fits on the front and back of the sign.

🗑 Possibility of mounting on an acrylic backer with the cables hollowed out inside.

SPECIFIC REQUEST

Thanks to our excellent savoir-faire, we can offer you a wide range of customisation options. Contact our team to find out more!

K≪∧ LISIG N